

PageCounter Professional™

Technical Specification Data

GENERAL INFORMATION

- Display:**
 - Full Color 640 x 480 Display
- Keyboard:**
 - Standard full alpha keyboard
 - Numeric keypad on keyboard
 - 3 large feature keys (Search, Scan & Recall) - See image at right
- Connectivity:**
 - Ethernet Category 5 cabling
 - No RS422 Support
 - Dual 10/100 Ethernet ports
- Storage:**
 - 128MB Compact Flash for offline storage
 - Stores over 10,000 Transactions
 - Stores 200,000 validation codes
- RAM:**
 - 64 MB RAM
- Operating System:**
 - Microsoft® Embedded Windows CE technology
- Bypass Functionality:**
 - Bypass keys allow usage of device while still capturing transactions
- Mounting:**
 - Optional wall mount available
 - Optional Floor stand available
- Power Supply:**
 - Includes dual voltage power supply
 - Input 100/240VAC, 50-60Hz, 0.5A
 - Output +5VDC/3000mA



PageCounter Professional Terminal



PageCounter Professional Terminal
(top view)



PageCounter Professional Terminal
(rear view)

Size:

	Packaged	Unpackaged
Screen down	15.25 x 5.5 x 11 in. 39 x 14 x 28 cm	8.27 x 3.55 x 11.82 in. 21 x 9 x 30 cm
Screen up		8.27 x 9.65 x 11.82 in. 21 x 24.5 x 30 cm

Weight:

	Packaged	Unpackaged
No Fax (PCP Copy)	6.00 lbs. / 2722 g	3.18 lbs. / 1446 g
1 Fax	6.25 lbs. / 2835 g	3.35 lbs. / 1524 g
2 Fax	6.45 lbs. / 2926 g	3.70 lbs. / 1680 g

PAGECOUNTER PROFESSIONAL TERMINALS

Options:

- Fax support
- Dual fax support
- Disbursement entry
- MyPrint™ support for secure print release
- Scan support
- Magnetic stripe card support
- Supports standard ANSI Track 2 magnetic stripe cards

Copy Details:

- Uses a proprietary Equitrac copier interface cable
- Connects to DB 26 connector on control terminal

Fax Details:

- Standard G3 support
- Full Super G3 (v.34) support
- Dual Fax line support

Scan Details:

- Supports Scan Integration
- eCopy ScanStation version 7.1 or higher

Disbursement Details:

- Supports multiple disbursement types
- Manual entry of transactions

MyPrint Details:

- Permits secure print release from terminal

Software Support:

Works in conjunction with:

- Equitrac Professional Enterprise Edition v.4.6 or higher
- Equitrac Professional v.3.5 or higher
- Equitrac System 4 v.3.2 - v.4.5

Service:

- Remote serviceability via WebAdmin tool
- Update software & firmware
- Reconfigure terminal
- Upload new validation tables
- Test & reboot capability

General Features

Terminal Display lines	640x480
Data storage capacity (STD/MAX)	128MB
QWERTY keyboard support	✓
Numeric keypad support	✓
Large function keys	✓
Transactions backed up at terminal	✓
Maximum number of devices controlled by a terminal	3
TCP/IP Support	✓
Dual Ethernet 10/100 ports	✓

Checklist

Communications

Fax V.34 Support	✓
RS 422 Support	
Backup to avoid losing transactions	✓

Capabilities

SEARCH, SCAN, and RECALL features	✓
Global RECALL (<i>recall last transactions from any terminal on network</i>)	✓
SPEED CODES - User definable	✓
Number of client matter descriptions viewed on screen	17
Job interrupt capability	✓
SmartPrompt™ support for conditional fields	✓
Configurable "Pick Lists" for all entries	✓
Dedicated help key	✓

Advanced Software Features

Alternate modes of operation for disbursements, etc.	✓
Store entire validation table with descriptions	✓
Maximum number of data entry fields per mode of operation	16
Audible time-out warning	✓
Historical Fax Transmission Look-up	✓
10/100 Ethernet TCP/IP Communications	✓
Shared Device Capable (copy + fax)	✓
Shared Device Capable (fax + fax)	✓
Shared Device Capable (copy + fax + fax)	✓

1000 South Pine Island Road, Suite 900, Plantation, FL 33324

P +1.800.327.0183 | F +1.954.475.7295 | www.equitrac.com

©2003 Equitrac Corporation. All rights reserved. Equitrac and PageCounter Professional are registered trademarks of Equitrac Corporation. All other brands and their products are trademarks or registered trademarks of their respective holders and should be noted as such. Companies, names and/or data used in screens and sample output are fictitious, unless otherwise noted.
MADE IN THE U.S.A.

LTPEQ109-1103

